

HYDRAULIC FLUID DATA SHEET



Check with Beck

FS11 HF

252-0028



This Premium Fully Synthetic Hydraulic Fluid is a superior quality formulation of state-of-the-art additives and carefully selected, high performance synthetic base oils for specific European nameplate motor vehicles. Specifically developed for use in hydraulically supported lever control, power steering and shock absorbers.

Specific to vehicles requiring FS11 Hydraulic Fluid. Check owner's manual for proper application.

This fully synthetic hydraulic fluid has outstanding viscosity/temperature behavior providing reliable operation at both high and low temperatures. It has excellent aging and oxidation stability, due to the carefully selected synthetic base oils with excellent sealing compatibility.

FORMULATED FOR	OE REFERENCE NUMBER
AUDI/VOLKSWAGEN	G 004 000 M2
BMW/MINI	83 29 0 429 576
JAGUAR	JLM21112
LAND ROVER	LR003401
MERCEDES-BENZ	001 989 24 03 10
PORSCHE	000 043 206 56 000 043 305 74
SAAB	93 16 0548
VOLVO	30741424

Reference CHF 202 or CHF 115

252-0028 (FS11 HF) Premium Synthetic Hydraulic Fluid must not be mixed with any glycol or silicone based fluids (i.e. brake fluids DOT 3/4/5.1 or DOT5)

SPECIFICATIONS & APPROVALS	
DIN	51 524 T3
ISO	7308
AUDI/ VOLKSWAGEN	TL 52 146
MERCEDES-BENZ	MB 345.0

ATTRIBUTES	
APPEARANCE	Green
FLASH POINT°C (°F)	>145°C
VISCOSITY AT -40°C	1400 mPas
VISCOSITY AT 40°C	19 mm ² /s
VISCOSITY AT 100°C	6.4 mm ² /s
DENSITY AT 15°C	0.835
SERVICE TEMPERATURE RANGE	-40°C to 130°C



Braking | Engine: Electrical | Engine: Mechanical | Fluids | Steering/Suspension/Driveline



©2018 Federal-Mogul Motorparts LLC. Beck/Arnley is a trademark owned by Federal-Mogul LLC or one or more of its subsidiaries in one or more countries. All other trademarks shown are the property of their respective owners. BA18XXXX

BeckArnley.com